

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Trade Multi-Purpose Silicone

Revision: 28/08/2018

Page 1 from 3

Reference nr DOP: 231459

Unique identification code of the product type:

Soudal Trade Multi-Purpose Silicone

Intended use or uses of the construction product:

Sealants used for sanitary applications.

Construction product in accordance with applicable harmonised specifications:

EN 15651-3:2012: Type S: CLASS S1

System or systems of assessment and verification of consistency of performance of the construction product, as set out in Annex V:

System 3: for essential characteristics

System 4: for reaction to fire

Name and contact address of the manufacturer as required pursuant to Article 11(5):

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

The notified body:

IFT Rosenheim GmbH, NB 0757 has carried out Determination of the Product Type under system 3.

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Trade Multi-Purpose Silicone

Revision: 28/08/2018

Page 2 from 3

Declared Performance: EN 15651-3:2012

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class F	EN 15651-3:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Microbiological growth	0	
Durability	Pass	

Conditioning:

Method A

Test substrate:

Aluminium

Glass

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by



Ing. W. Dierckx

Technical Product Manager
B-2300 Turnhout, Belgium, 28/08/2018

CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Revision: 28/08/2018

Page 3 from 3



NB 0757

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

18

Reference nr DOP: 231459

EN 15651-3: 2012

Sealants used for sanitary applications.

Soudal Trade Multi-Purpose Silicone

EN 15651-3:2012: Type S: CLASS S1

Conditioning:
Method A
Substrate:
Aluminium
Glass

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class F	EN 15651-3: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Elongation at break	≥ 25%	
Microbiological growth	0	
Durability	Pass	