

DECLARATION OF PERFORMANCE



Bond It Ceramic Tile Adhesives

EN12004:2007 +A1:2012
 Attestation Level 3a and 3
 Initial testing performed by notified body 1289

Improved Dispersion Based Tile Adhesives for Internal Tiling

| | |
|--|----------------------------------|
| | Fix'n'Grout BDTA10,11 |
| | D2 |
| Bond Strength | |
| Initial Shear Adhesion Strength | ≥1N/mm ² |
| Durability | |
| Shear Adhesion Strength after Heat Ageing | ≥1N/mm ² |
| Shear Adhesion Strength at Elevated Temperatures | ≥1N/mm ² |
| Shear Adhesion Strength after Water Immersion | ≥0.5N/mm ² |
| Reaction To Fire | Class E |
| Release of Dangerous Substances | See MSDS |

Improved Dispersion Based Tile Adhesives with reduced slip for Internal Tiling

| | |
|--|---|
| | Aqua-Tile BDTA01, 02, 03 |
| | D2T |
| Bond Strength | |
| Initial Shear Adhesion Strength | ≥1N/mm ² |
| Durability | |
| Shear Adhesion Strength after Heat Ageing | ≥1N/mm ² |
| Shear Adhesion Strength at Elevated Temperatures | ≥1N/mm ² |

| | |
|---|-----------------------|
| Shear Adhesion Strength after Water Immersion | ≥0.5N/mm ² |
| Reaction To Fire | Class E |
| Release of Dangerous Substances | See MSDS |

Dispersion Based Tiles Adhesives with reduced slip for Internal Tiling

| | Premium CTA BDTA17,18 | SuperGrip BDTA07,08,06 |
|---|--------------------------|---------------------------|
| | D1T | D1T |
| Bond Strength | | |
| Initial Shear Adhesion Strength | ≥1N/mm ² | ≥1N/mm ² |
| Durability | | |
| Shear Adhesion Strength after Heat Ageing | ≥1N/mm ² | ≥1N/mm ² |
| Reaction To Fire | Class E | Class E |
| Release of Dangerous Substances | See MSDS | See MSDS |

Improved Fast Setting Cementitious Tile Adhesive for Internal Tiling

| | Rapid-Flex BDTRF/ BDTRFWH |
|---|---------------------------------|
| | C2F |
| Bond Strength | |
| Early Tensile Adhesion Strength | ≥0.5N/mm ² |
| Initial Tensile Adhesion Strength | ≥1N/mm ² |
| Durability | |
| Tensile Adhesion Strength after Water Immersion | ≥1N/mm ² |
| Reaction To Fire | Class E |
| Release of Dangerous Substances | See MSDS |

Fast Setting Cementitious Tile Adhesive for Internal Tiling

| | Rapid-Set BDTRS |
|-----------------------------------|-----------------------|
| | C1F |
| Bond Strength | |
| Early Tensile Adhesion Strength | ≥0.5N/mm ² |
| Initial Tensile Adhesion Strength | ≥0.5N/mm ² |
| Durability | |

| | |
|---|-----------------------|
| Tensile Adhesion Strength after Water Immersion | ≥0.5N/mm ² |
| | |
| Reaction To Fire | Class E |
| Release of Dangerous Substances | See MSDS |

Improved cementitious tile adhesive with reduced slip and extended open time. Deformable.

| | |
|---|--|
| | CTA Flexible BDCTAF, GR C2TE S2 |
| Bond Strength | |
| Tensile adhesion strength after 30 minutes | ≥0.5 N/mm ² |
| Initial tensile adhesion strength | ≥1.0 N/mm ² |
| Durability | |
| Tensile adhesion strength after water immersion | ≥1.0 N/mm ² |
| Tensile adhesion strength after heat aging | ≥1.0 N/mm ² |
| Tensile adhesion strength after freeze/thaw | ≥1.0 N/mm ² |
| | |
| Slip | ≤ 0.5 mm |
| Transverse deformation | ≥2.5 mm |
| | |
| Reaction to fire | Class E |
| Release of dangerous substances | See MSDS |



Simon Hodgson
Technical Manager

Seal It Services Ltd T/As Bond It
Unit G16 River Bank Way,
Lowfields Business Park,
Elland,
West Yorkshire, HX5 9DN
United Kingdom

Issue 5: 2nd March 2021

DECLARATION OF PERFORMANCE



Bond It Ceramic Tile Adhesives

EN12004:2007 +A1:2012
Attestation Level 3a and 3
Initial testing performed by notified body 1289

Improved Dispersion Based Tile Adhesives for Internal Tiling

| | |
|--|----------------------------------|
| | Fix'n'Grout BDTA10,11 |
| | D2 |
| Bond Strength | |
| Initial Shear Adhesion Strength | ≥1N/mm ² |
| Durability | |
| Shear Adhesion Strength after Heat Ageing | ≥1N/mm ² |
| Shear Adhesion Strength at Elevated Temperatures | ≥1N/mm ² |
| Shear Adhesion Strength after Water Immersion | ≥0.5N/mm ² |
| Reaction To Fire | Class E |
| Release of Dangerous Substances | See MSDS |

Improved Dispersion Based Tile Adhesives with reduced slip for Internal Tiling

| | |
|--|---|
| | Aqua-Tile BDTA01, 02, 03 |
| | D2T |
| Bond Strength | |
| Initial Shear Adhesion Strength | ≥1N/mm ² |
| Durability | |
| Shear Adhesion Strength after Heat Ageing | ≥1N/mm ² |
| Shear Adhesion Strength at Elevated Temperatures | ≥1N/mm ² |

| | |
|---|-----------------------|
| Shear Adhesion Strength after Water Immersion | ≥0.5N/mm ² |
| Reaction To Fire | Class E |
| Release of Dangerous Substances | See MSDS |

Dispersion Based Tiles Adhesives with reduced slip for Internal Tiling

| | Premium CTA BDTA17,18 | SuperGrip BDTA07,08,06 |
|---|--------------------------|---------------------------|
| | D1T | D1T |
| Bond Strength | | |
| Initial Shear Adhesion Strength | ≥1N/mm ² | ≥1N/mm ² |
| Durability | | |
| Shear Adhesion Strength after Heat Ageing | ≥1N/mm ² | ≥1N/mm ² |
| Reaction To Fire | Class E | Class E |
| Release of Dangerous Substances | See MSDS | See MSDS |

Improved Fast Setting Cementitious Tile Adhesive for Internal Tiling

| | Rapid-Flex BDTRF/ BDTRFWH |
|---|---------------------------------|
| | C2F |
| Bond Strength | |
| Early Tensile Adhesion Strength | ≥0.5N/mm ² |
| Initial Tensile Adhesion Strength | ≥1N/mm ² |
| Durability | |
| Tensile Adhesion Strength after Water Immersion | ≥1N/mm ² |
| Reaction To Fire | Class E |
| Release of Dangerous Substances | See MSDS |

Fast Setting Cementitious Tile Adhesive for Internal Tiling

| | Rapid-Set BDTRS |
|-----------------------------------|-----------------------|
| | C1F |
| Bond Strength | |
| Early Tensile Adhesion Strength | ≥0.5N/mm ² |
| Initial Tensile Adhesion Strength | ≥0.5N/mm ² |
| Durability | |

| | |
|---|-----------------------|
| Tensile Adhesion Strength after Water Immersion | ≥0.5N/mm ² |
| Reaction To Fire | Class E |
| Release of Dangerous Substances | See MSDS |

Improved cementitious tile adhesive with reduced slip and extended open time. Deformable.

| | CTA Flexible BDCTAF, GR C2TE S2 |
|---|--|
| Bond Strength | |
| Tensile adhesion strength after 30 minutes | ≥0.5 N/mm ² |
| Initial tensile adhesion strength | ≥1.0 N/mm ² |
| Durability | |
| Tensile adhesion strength after water immersion | ≥1.0 N/mm ² |
| Tensile adhesion strength after heat aging | ≥1.0 N/mm ² |
| Tensile adhesion strength after freeze/thaw | ≥1.0 N/mm ² |
| Slip | ≤ 0.5 mm |
| Transverse deformation | ≥2.5 mm |
| Reaction to fire | Class E |
| Release of dangerous substances | See MSDS |



Simon Hodgson
Technical Manager

Seal It Services Ltd T/As Bond It
Unit G16 River Bank Way,
Lowfields Business Park,
Elland,
West Yorkshire, HX5 9DN
United Kingdom

Issue 1: 20th October 2022