

DECLARATION OF PERFORMANCE

**DoP No: S55001026-0043**

1. Unique identification code of product-type:  
**OB1 Multi-Surface Construction Sealant & Adhesive - Colours**
2. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:  
**Sealants for façade elements**  
**Sealants for sanitary joints**  
**Sealants for pedestrian walkways**  
**EN 15651-1:2012 : F-EXT-INT-CC (CLASS 25HM)**  
**EN 15651-3 : 2012: S (CLASS XS2)**  
**EN 15651-4 :2012: PW-EXT-INT-CC (CLASS 25 HM)**
3. Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):  
**SIROFLEX LIMITED ■ DODWORTH BUSINESS PARK, DODWORTH, BARNSELY, S. YORKS ■ S75 3SP**
4. System or systems of assessment and verification of constancy of performance:  
**System 3**
5. Designated Standards  
**EN 15651-1 / EN 15651-3 / EN 15651-4**
6. Approved Body  
**2538, 4ward Testing Ltd**

7. Declared performance:

Conditioning: Procedure B  
 Substrate: Mortar M1 (with primer MSP)

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire (EN ISO 11925-2:2020)	<b>Class E</b>	<b>EN 15651-1:2012</b>
Release of chemicals dangerous to the environment and health	<b>NPD (*)</b>	
<b>Water tightness and air tightness</b>		
Resistance to flow (EN ISO 7390)	<b>≤ 3 mm</b>	
Loss of volume (EN ISO 10563)	<b>≤ 10 %</b>	
Tensile properties at maintained extension after water immersion (EN ISO 10563)	<b>NF</b>	
Tensile properties (secant modulus) for use in cold climate areas (-20°C) (EN ISO 8340)	<b>NR</b>	
Tensile properties at maintained extension for use in cold climate areas (-30°C) (EN ISO 8340)	<b>NF</b>	
<b>Durability</b>	<b>Pass</b>	

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire (EN ISO 11925-2:2020)	<b>Class E</b>	<b>EN 15651-3:2012</b>
Release of chemicals dangerous to the environment and health	<b>NPD (*)</b>	
<b>Water tightness and air tightness</b>		
Vertical flow resistance (EN ISO 7390)	<b>≤ 3 mm</b>	
Loss of volume (EN ISO 10563)	<b>≤ 20 %</b>	
Tensile properties at maintained extension after water immersion (EN ISO 10590)	<b>NF</b>	
Microbiological growth (EN ISO 846)	<b>NPD</b>	
<b>Durability</b>	<b>Pass</b>	

<b>Essential characteristics</b>	<b>Performance</b>	<b>Harmonized technical specification</b>
Reaction to fire (EN ISO 11925-2:2020)	<b>Class E</b>	<b>EN 15651-4:2012</b>
Release of chemicals dangerous to the environment and health	<b>NPD (*)</b>	
<b>Water tightness and air tightness</b>		
Tensile properties at maintained Extension (EN ISO 8339)	<b>≤ 3 mm</b>	
Loss of volume (EN ISO 10590)	<b>≤ 10 %</b>	
Tear resistance (EN ISO 8340)	<b>NF</b>	
Tensile properties (secant modulus) for use in cold climate areas (-20°C ) (EN ISO 8340)	<b>NF</b>	
Tensile properties at maintained extension for use in cold climate areas (-30°C ) (EN ISO 8340)	<b>NR</b>	
<b>Durability</b>	<b>Pass</b>	

(\*) See material safety data sheet  
NPD: No Performance Determined  
NF: No Failure  
NR: Not required

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Ashley Greenwood  
HSE Manager  
Siroflex Limited

December 2019