

EVO-STIK THE DOG'S B*LL*CKS

MULTI-PURPOSE ADHESIVE & SEALANT

Date: 26 March 2021 TDS Number: TDS01979

YOUR SMART ADVANTAGES

- Advanced Hybrid SMP technology; multi-purpose adhesive & sealant – eliminates the need for numerous adhesives and sealants.
- High strength adhesive and anti-mould sealant perfect for kitchens and bathrooms.
- Weatherproof, waterproof, UV resistant, overpaintable and available in 6 colours including Crystal.

USES

EVO-STIK THE DOG'S B*LL*CKS is specially formulated using advanced hybrid SMP technology and is designed to eliminate the need for numerous adhesives and sealants. EVO-STIK THE DOG'S B*LL*CKS is solvent free and suitable for bonding a variety of materials used both indoors and outdoors. EVO-STIK THE DOG'S B*LL*CKS can be used for sealing joints with low ability to absorb movement. It can also be used for gap-filling, roof repair and as a decorators caulk.

PRODUCT CHARACTERISTICS	
Colour/ Product Code	White: 30610662
	Black: 30610593
	Grey: 30610595
	Ivory: 30610596
	Brown: 30610688
	Crystal: 30610687
Base	Silane-terminated polymers, neutrally cross-linked
Specific Gravity	1.1 at 23°C and 50% relative humidity
Curing Method	Moisture Curing

Storage/Shelf Life	18 months from the date of manufacture (12 months for Crystal) when stored in the dry between +5°C & +25°C, out of direct sunlight. Protect from frost.
TYPICAL PERFORMANCE DATA (Approx.)	
Application	+5°C to +40°C
Service Temperature	-40°C to +100°C
Coverage	Approx. 14 linear metres of 5mm diameter bead per C20 cartridge
Drying Times	Skin Formation: 15 minutes dependent on temperature & humidity.
	Through Dry: Approx. 2mm per 24 hours and 50% relative humidity.
	Always tool sealant within 20 minutes of application.
Movement Capability	15%, relative to the initial width of the joint
Elongation	Approx. 250%

Bostik Ltd., Common Road, Stafford, ST16 3EH,

Tel: +44 (0) 1785 272625 www.bostik.com/uk

Bostik, Evo-Stik are registered trademarks of Bostik Ltd.

DIRECTIONS FOR USE

Before using EVO-STIK THE DOG'S B*LL*CKS refer to the relevant Health & Safety Data Sheet. Available at **www.bostik.com/uk** named as the code stated.

PREPARATION

Surfaces must be clean, sound and free from dust or any loose material.

APPLICATION

- Unscrew the nozzle, and using a sharp knife, cut off the dome of the cartridge, taking care not to damage the thread. Screw the nozzle onto the cartridge.
- 2. Cut off the tapered end of the nozzle at a 45° angle, to a width matching the gap to be sealed.
- 3. Fit the cartridge into the cartridge gun by pressing the release plate and pulling out the plunger. Insert cartridge and repeatedly squeeze the trigger until the product appears.

(For Adhesive Application)

4. Apply parallel beads of adhesive to one of the surfaces, align and bring the surfaces together within 10 minutes.

(For Sealant Application)

- 5. Place the nozzle at the start of the gap, and gently squeeze the trigger. Push forward slowly, ensuring that contact is made by the product with both sides of the gap. At the end of the run, release the trigger and press the plunger release plate of the gun.
- 6. Product must be gunned firmly into the joints to ensure good adhesion to the joint surfaces.
- 7. Smooth the sealant with a wet, round ended tool (do not use a wetted finger), remove any excess with a cloth moistened with white spirit.
- 8. After use, ensure the cap is replaced to prevent nozzle from clogging.

CLEANING

Uncured product may be removed using cloths lightly dampened with white spirit, after carefully scraping off the bulk. Cured product requires mechanical removal.

PRECAUTIONS IN USE

EVO-STIK THE DOG'S B*LL*CKS cannot be applied to surfaces which have frost or ice on them. Do not use on polyolefines (eg. PE, PP), polyhalogenolefines (eg. Teflon $^{\rm m}$) and similar plastics. Will not resist abrasion in floor joints. Do not use in swimming pools. Do not use for aquarium applications. Prevent entry of uncured sealant into drains or watercourses. Do not use on or against bitumen. Not suitable for bedding double glazed/insulating glass units into frames. Do not submerge under water.

For any application not covered please contact technical services on +44 (0) 1785 272625.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for EVO-STIK THE DOG'S B*LL*CKS.



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

SalesTel: 0844 371 1192Fax: 01785 241818customer.service@bostik.comTechnical AdviceTel: 0844 371 1197Fax: 01785 272867technical.service@bostik.comTechnical Data & COSHH (MSDS) Data SheetsTel: 01785 272625Fax: 01785 212962stafford.gatehouse@bostik.com